



Continuous Duty PowerSeal

Enter Complete Part Number Here →

Ordering Information • Custom features available upon request,
Contact your Trombetta sales rep before ordering.

-
X X X - X X X X - X X X

Family	Coil Connection Configuration	High Current Stud	Coil Voltage	Bracket Type	Bracket Location	Duty Cycle	Contact Material	Sealing
6- Power Seal	3- Grounded 10/32	4- Standard Power Seal	12- 12 Volt	1- L Bracket, Curved	1- Standard Location	0- 100% Continuous	1- Intermittent Duty & 12V Continuous Duty - Copper, 24, 36 & 48V Continuous Duty, Silver Alloy Stationary Contacts with Silver Alloy Plated Moveable Contacts.	2- Sealed Designed
	5- Grounded (1) 10-32 Stud + Spade		15- 15 Volt	2- Flat Bracket		2- 25%		
	8- Non-Grounded (2) 10/32	24- 24 Volt	3- Curve Bracket					
	9- Non-Grounded (2) 10-32 Stud+Spades	36- 36 Volt	4- 90 Degree Bracket					
			48- 48 Volt	5- L Bracket, Flat				
				6- L Bracket Curved Narrow				
				7- L Bracket Flat, Long				

N88 W13901 Main Street • Suite 200 • Menomonee Falls, WI 53051
p 262.251.5454 • f 262.251.5757 • email: sales@trombetta.com



www.trombetta.com