



AVAILABLE CONFIGURED COMPONENTS

HOUSINGS	PLUNGERS	RODS	"B" THREADS	"A" INSTALLED	BOOTS	CONNECTORS
E05204 Side Mount	F08473 1/4-20 Int. thrd.	E06488	1/4-20 Smooth rod	1.59"	F10225 Boot Kit Q514	
E05332 Base Mount	F08598 1/4-28 Int. thrd.	F08586	1/4-20 Smooth rod	2.65"		
		F08616	1/4-20 Smooth rod	2.06"		
		F08793	1/4-20 Smooth rod	1.94"		
		F08914	1/4-20 Smooth rod	3"		
		F09159	1/4-20 Smooth rod	1.31"		
		F09180	1/4-20 Smooth rod	2.25"		
		F09247	1/4-20 Smooth rod	1.78"		
		F09908	1/4-20 Smooth rod	4.03"		
		F09990	1/4-20 Smooth rod	4.31"		
		F10249	1/4-20 Smooth rod	2.53"		
		F10321	1/4-20 Smooth rod	2"		

AVAILABLE COILS WITH FORCE CHARACTERISTICS

VOLTS D.C.	COILS	OHM RATING	DUTY CYCLE	WATTS	FORCE @ 1"	FORCE @ .75"	FORCE @ .50"	FORCE @ .25"
12 v.	R05471	.23	5%	640	37 lb.	39 lb.	40 lb.	50 lb.
	R04746	.331	7%	435	27 lb.	30 lb.	32 lb.	42 lb.
	R05305	3.9	81%	37	2.5 lb.	3.2 lb.	4.5 lb.	8.5 lb.
24 v.	R04746	.331	2%	1740	61 lb.	61 lb.	62 lb.	71 lb.
	R05305	3.9	20%	148	11 lb.	15 lb.	18 lb.	26 lb.
	R04796	8.8	46%	65	4.8 lb.	6.1 lb.	8 lb.	15 lb.
	R04668	19	100%	30	1.2 lb.	1.5 lb.	2.2 lb.	5.8 lb.
108 v.	R05305	3.9	1%	2991	82 lb.	82 lb.	82 lb.	90 lb.
	R04858	14.2	4%	821	41 lb.	42 lb.	45 lb.	54 lb.
	R04668	19	5%	614	32 lb.	34 lb.	36 lb.	45 lb.
	R04757	35	9%	333	22 lb.	25 lb.	28 lb.	37 lb.
	R04846	70	18%	167	10 lb.	13 lb.	17 lb.	23 lb.
	R05107	334	85%	35	1.8 lb.	2.5 lb.	3.5 lb.	7.3 lb.
216 v.	R04858	14.2	1%	3266	85 lb.	85 lb.	85 lb.	92 lb.
	R04668	19	1%	2456	70 lb.	70 lb.	71 lb.	79 lb.
	R04757	35	2%	1333	52 lb.	53 lb.	57 lb.	64 lb.
	R04846	70	5%	667	33 lb.	35 lb.	37 lb.	46 lb.
	R05107	334	21%	140	9.6 lb.	13 lb.	15 lb.	23 lb.