

Ag Implement Flasher Module

This enhanced lighting module features integrated automotive connectors to provide a cost effective and heavy duty solution to meet the ASAE standard for Ag lighting.



Product Features

- Works with 12V or 24V systems
- No wires
- Up to 10.0A per output
- Small footprint
- Potted-Protection from Harsh Environments
- Sealed automotive connectors
- Easy 2 Point Mounting / rugged ABS housing
- RoHS compliant
- Customizable
- For use with incandescent or LED

Specifications

Power Supply Voltage: 9-32 VDC
Output Current: 10.0A Max
Storage Temp.: -40° to 85°C
Operating Temp.: -40° to 85°C
IP Rating: 67
Weight: 0.17 lbs. Typ

Unit Connections

12015798 DELPHI

- Pin A: Ground from tractor
- Pin B: Right turn input from tractor
- Pin C: Left turn input from tractor
- Pin D: Tail light input from tractor

12010975 DELPHI

- Pin A: Right turn enhanced output
- Pin B: Right turn and flasher output
- Pin C: Left turn and flasher output
- Pin D: Tail light output
- Pin E: Ground
- Pin F: Left turn enhanced output

Note: This flasher module does not include the mate connectors or wire harnesses. Trombetta can provide these components when requested.

Normal Driving Operation

Red tail lamps (low) "ON" if activated on tractor.
Amber warning lamps flash in unison with tractor.

Turning Operation

Red tail lamp (high) and amber warning lamp opposite the direction of turn are "ON". Amber warning lamp in direction of turn flashes in unison with the tractor. Red tail lamp (high) in direction of turn flashes in unison with the amber warning lamp.

